



Certificate number: 2203756 (1)

Issued 31/03/2022
Expires 31/03/2027

Kiwa Type 2 Thermostatic Mixing Valve and KUKreg4 Certification

Evaluation Guideline - Kiwa UK – EG001 – Thermostatic mixing valves
Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)
Model number(s) – see Appendix

Crosswater Ltd

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

EN 1111 Type 2 Thermostatic mixing valves(high pressure).

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/products/tmv-testing/> to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Crosswater Ltd
Lake view house
Rennie drive
Dartford
DA1 5FU



Product Certificate

Appendix to Certificate number: 2203756

The following products belong to this certificate

Reference:	S210685, S2203145, 2201704
Product description:	Wall mounted concealed thermostatic shower valves, 1, 2 and 3 way valves incorporating diverter mechanism as appropriate.
Models:	1 outlet portrait WLBP1000RC+, WLBP1000R+; 1 outlet landscape WLBP1001RC+, WLBP1001R+; 2-way diverter portrait WLBP1500RC+, WLBP1500R+; 2-way diverter landscape WLBP1501RC+, WLBP1501R+; 2 outlet independent portrait WLBP2000RC+, WLBP2000R+; 2 outlet independent landscape WLBP2001RC+, WLBP2001R+; 3-way diverter portrait WLBP2500RC+, WLBP2500R+; 2-way diverter multi-flow portrait WLBP25X3R+; 2-way diverter multi-flow landscape WLBP25X31R+; 3-way with 2-way diverter portrait WLBP3000RC+, WLBP3000R+; 3-way with 2-way diverter landscape WLBP3001RC+, WLBP3001R+. RC+ have a chrome collar R+ are without a chrome collar.
Size:	3/4 BSP Female
Designation of Use:	HP-S
Marking:	Inlets marked with red and blue marker, valve body embossed CW1, 2 or 3 +1 and printed with a stylized X (Crosswater logo). Front fascia plate laser etched with a stylized X.
Materials:	Non-metallic materials assessed (BS 6920) to point of discharge.
Backflow protection notes:	Inlets fitted with SCV
Additional notes:	Inlets fitted with strainers

Extra Notes: