



Certificate number: 2412747 (1)

Issued 19/12/2024

Expires 06/12/2029

## Kiwa Type 3 Thermostatic Mixing Valve and KUKreg4 Certification

Evaluation Guideline - Kiwa UK – EG001 – Thermostatic mixing valves

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

### Herz Valves Ltd

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

**The DoH: Health Technical Memorandum 04-01: Supplement Performance specification D 08: thermostatic mixing valves (healthcare premises) 2017.**

**Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.**

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory  
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/products/tmv-testing/> or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec  
(A Trading Division of Kiwa Ltd)  
26A Rassau Industrial Estate  
Ebbw Vale  
Gwent  
NP23 5SD  
United Kingdom  
T +44 (0)1495 308185  
[uk.water@kiwa.com](mailto:uk.water@kiwa.com)  
[www.kiwa.co.uk](http://www.kiwa.co.uk)

Certificate Issued to:  
**Herz Valves Ltd**  
**Unit 2B**  
**Centurian Business Park**  
**Sturrock Way**  
**Bretton**  
**Peterborough**  
**PE3 8YF**



# Product Certificate

Appendix to Certificate number: 2412747

The following products belong to this certificate

<b>Reference:</b>	S2402099 & 2412747
<b>Product description:</b>	Range of 'T' type thermostatic mixing valves with brushed chrome DZR brass body having round body design. Hot and Cold inlet connections incorporate single check valve cartridges and stainless-steel strainers. IV versions incorporate ¼ turn servicing valve.
<b>Models:</b>	HVTMV-15 HVTMV-22 HVTMV-15IV HVTMV-22IV
<b>Size:</b>	15mm & 22mm compression inlet/outlet connections.
<b>Designation of Use:</b>	HP-B HP-S HP-W LP-B LP-S LP-W
<b>Marking:</b>	Inlets embossed H and C, body embossed with Caleffi logo and CR mark. Headwork under a red cap printed Herz HVTMV. Cap printed Herz.
<b>Materials:</b>	Non-metallic materials assessed (BS 6920) to the point of discharge.
<b>Backflow protection notes:</b>	Thermostatic valves with tails incorporate SCV's at each inlet.